

uscita umidificatore Ø mm humidifier outlet Ø mm				heaterSteam										
				30 (1.2")					40 (1.6")			2x 40 (1.6")		
capacità umidificatore kg/h humidifier capacity kg/h				2	4	6	10	13	20	27	40	53	60	80
ingresso distributore (øA) mm (in) distributor inlet (øA) mm (in)	capacità max. distributore kg/h (lbs/h) max. distributor capacity kg/h (lbs/h)	min. larghezza condotta/AHU mm (in) min. width of duct/AHU mm (in)	codice code	UR002	UR004	UR006	UR010	UR013	UR020	UR027	UR040	UR053	UR060	UR080
30 (1.2")	5 (11)	350 (13.7")	DP035D30RH	1	1									
30 (1.2")	8 (17.6)	450 (17.7")	DP045D30RH	1	1	1								
30 (1.2")	12 (26.4)	600 (23.6")	DP060D30RH		1	1	1		(2)*					
30 (1.2")	18 (39.6)	850 (33.5")	DP085D30RH		1	1	1	1	(2)*	(2)*				
30 (1.2")	18 (39.6)	1050 (41.3")	DP105D30RH		1	1	1	1	(2)*	(2)*				
30 (1.2")	18 (39.6)	1250 (49.2")	DP125D30RH		1	1	1	1	(2)*	(2)*				
30 (1.2")	18 (39.6)	1650 (65")	DP165D30RH				1	1	(2)*	(2)*				
40 (1.6")	25 (55)	850 (33.5")	DP085D40RH						1	1	(2)**	(4)**	(4)**	(4)**
40 (1.6")	35 (77)	1050 (41.3")	DP105D40RH						1	1	(2)**	2	2	(4)**
40 (1.6")	45 (99)	1250 (49.2")	DP125D40RH						1	1	1	2	2	2
40 (1.6")	45 (99)	1650 (65")	DP165D40RH						1	1	1	2	2	2
40 (1.6")	45 (99)	2050 (80.7")	DP205D40RH								1	2	2	2

uscita umidificatore Ø mm humidifier outlet Ø mm				gaSteam		
				2x 40 (1.6")		4x 40 (4x 1.6")
capacità umidificatore kg/h humidifier capacity kg/h				45	90	180
ingresso distributore (øA) mm (in) distributor inlet (øA) mm (in)	capacità max. distributore kg/h (lbs/h) max. distributor capacity kg/h (lbs/h)	min. larghezza condotta/AHU mm (in) min. width of duct/AHU mm (in)	codice code	UG045	UG090	UG180
30 (1.2")	5 (11)	350 (13.7")	DP035D30RH	2	2	4
30 (1.2")	8 (17.6)	450 (17.7")	DP045D30RH			
30 (1.2")	12 (26.4)	600 (23.6")	DP060D30RH			
30 (1.2")	18 (39.6)	850 (33.5")	DP085D30RH			
30 (1.2")	18 (39.6)	1050 (41.3")	DP105D30RH			
30 (1.2")	18 (39.6)	1250 (49.2")	DP125D30RH			
30 (1.2")	18 (39.6)	1650 (65")	DP165D30RH			
40 (1.6")	25 (55)	850 (33.5")	DP085D40RH			
40 (1.6")	35 (77)	1050 (41.3")	DP105D40RH	2	(4)**	
40 (1.6")	45 (99)	1250 (49.2")	DP125D40RH	2	(4)**	
40 (1.6")	45 (99)	1650 (65")	DP165D40RH	2	2	4
40 (1.6")	45 (99)	2050 (80.7")	DP205D40RH	2	2	4

Дополнительную информацию можно получить в Представительстве компании CAREL в Москве и Санкт-Петербурге:
www.carelrussia.com

